

# **29582**

Model Number: Category: Sub Category: Power Configuration: Physical Configuration: BR100-1025 Basic Standard 20A, 120V, 1.9kW 19 in / 483 mm, Horizontal



Description:	The 29582 functions as a basic power strip without built-in surge protection. This unit is ideal for installations in facilities with proper surge protection at the main electrical service entrance. 29582 - Basic, Standard, 20A, 120V, Horizontal, (10) NEMA 5-20R, power switch, breakered, 10 ft power cord with 5-20P, Black Powder Coat.	
Product Summary:		
Plug Form:	Receptacle: NEMA 5-20R (Quantity: 10)	
Chassis Colors Options:	To discuss color options, contact your local sales representative.	

## **Geist Americas**

800.432.3219 geistglobal.com 1.877.449.4150 geistglobal.com

#### Geist Europe

+44 (0) 1823.275100 geistglobal.com Geist Asia

China +86.755.86639505 geistglobal.com



# **Product Specification and Options:**

Quantity Of Inputs	1
Voltage	120V
Current	20A
VA per Input (Load Capacity)	1.9kW
Frequency	50/60 Hz
Over Current Protection	20A Thermal Breaker
Switch	Yes
Indicators - LED(s)	1 - Power ON Green LED
Power Cable Wire Gauge	12/3
Power Cable Length	10ft
Plug Type	NEMA 5-20P
Receptacle/Socket Type #1	NEMA 5-20R
- Quantity on Rear	10
- Quantity per Breaker	10
- Style	Duplex
- Maximum Output per Receptacle/Socket	20A
- Voltage per Receptacle/Socket	120V
Continuous Operating Temperature Range	10-45C / 50-113F
Heavy Steel - Powder Coat Finish	Black
Configuration	19 in / 435 mm Horizontal Rackmount
Flush Mount	Yes
Made in the USA	Yes
Product Warranty	5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years
Certification/Agency Approvals	RoHS Compliant
Certification/Agency Approvals	UL & c-UL Listed 60950
Chassis Dimensions (HxWxD)	1.72in x 17in x 3.75in
Shipped Weight	6lbs (2.72kg)

#### Geist Americas

800.432.3219 qeistalobal.com

#### 1.877.449.4150 geistglobal.com

## Geist Europe

+44 (0) 1823.275100 geistglobal.com

#### Geist Asia

China +86.755.86639505 geistglobal.com