



3M N2530-6002-RB

Product Attributes		Select All	<input type="checkbox"/>
Categories	Connectors, Interconnects		<input type="checkbox"/>
	Rectangular Connectors - Headers, Male Pins		<input checked="" type="checkbox"/>
Manufacturer	3M		<input type="checkbox"/>
Series	2500		<input type="checkbox"/>
Packaging 	Bulk 		<input type="checkbox"/>
Part Status	Active		<input type="checkbox"/>
Connector Type	Header		<input type="checkbox"/>
Contact Type	Male Pin		<input type="checkbox"/>
Pitch - Mating	0.100" (2.54mm)		<input type="checkbox"/>
Number of Positions	30		<input type="checkbox"/>
Number of Rows	2		<input type="checkbox"/>
Row Spacing - Mating	0.100" (2.54mm)		<input type="checkbox"/>
Number of Positions Loaded	All		<input type="checkbox"/>
Style	Board to Board or Cable		<input type="checkbox"/>
Shrouding	Shrouded - 4 Wall		<input type="checkbox"/>
Mounting Type	Through Hole		<input type="checkbox"/>
Termination	Solder		<input type="checkbox"/>
Fastening Type	Push-Pull		<input type="checkbox"/>
Contact Length - Mating	0.243" (6.17mm)		<input type="checkbox"/>
Contact Length - Post	0.112" (2.84mm)		<input type="checkbox"/>
Overall Contact Length	-		<input type="checkbox"/>
Insulation Height	0.390" (9.91mm)		<input type="checkbox"/>
Contact Shape	Square		<input type="checkbox"/>
Contact Finish - Mating	Gold		<input type="checkbox"/>

Contact Finish Thickness - Mating	30.0µin (0.76µm)	<input type="checkbox"/>
Contact Finish - Post	Tin	<input type="checkbox"/>
Contact Material	Copper Alloy	<input type="checkbox"/>
Insulation Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled	<input type="checkbox"/>
Features	Keying Slot	<input type="checkbox"/>
Operating Temperature	-55°C ~ 105°C	<input type="checkbox"/>
Ingress Protection	-	<input type="checkbox"/>
Material Flammability Rating	UL94 V-0	<input type="checkbox"/>
Insulation Color	Black	<input type="checkbox"/>
Current Rating	1.75A	<input type="checkbox"/>
Voltage Rating	-	<input type="checkbox"/>
Mated Stacking Heights	-	<input type="checkbox"/>
Contact Finish Thickness - Post	200.0µin (5.08µm)	<input type="checkbox"/>
Applications	-	<input type="checkbox"/>