



1-1375192-3

**SL110 Series Modular Jack, 8-position, RJ11, category 3, unshielded, without dust cover, alpine white**

## Product Classification

Portfolio	NETCONNECT®
Product Series	SL Series
Product Type	Modular jack
Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America

## Dimensions

Depth	30.48 mm   1.20 in
Height	16.13 mm   0.64 in
Width	14.48 mm   0.57 in

## Electrical Specifications

ANSI/TIA Category	3
Current Rating, maximum	0.75 A
Safety Voltage Rating	150 Vac
Transmission Standard	ANSI/TIA-568-C.2   ISO/IEC 11801 Class C

## Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)

## General Specifications

Cable Type	U/UTP (unshielded)
Color	White
Diameter Insulated Conductor, maximum	1.450 mm
Diameter Outer Jacket, maximum	5.800 mm
Mount Type	SL Series faceplates and panels
Package Quantity	1
Packaging Type	Bag
Panel Cutout, recommended	14.78 x 20.07 mm (0.58 x 0.79 in)
Panel Thickness, recommended	1.60 mm

## Mechanical Specifications

1-1375192-3

Conductor Gauge, solid	24–22 AWG
Conductor Gauge, stranded	26–24 AWG
Conductor Type	Solid   Stranded
Material Type	Polycarbonate
Outlet Type	Standard
Outlet/Module Contact Base Material	Beryllium copper
Outlet/Module Contact Plating Thickness	1.27 µm
Outlet/Module Contact Plating Type	Gold
Rear Termination Type	IDC
Wiring	T568A   T568B

## Mechanical Specifications

Rear Termination Tool	SL Termination tool
-----------------------	---------------------

## Regulatory Compliance/Certifications

### Agency

RoHS 2011/65/EU

### Classification

Compliant