



Aerospace Part#: 1361

PLENUM CABLE

## DESCRIPTION

3 Conductors AWG 20/7x28 TC Unshield FEP/FEP Gray CL2P CMP

## PHYSICAL PROPERTIES

Conductors	Insulation					
# Conductors	AWG	Material	Material	Wall	Finished OD	
3	20/7x28	Tinned Copper	FEP	.007"	.052"	

Outer Jacket Material			Cabling	
Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Gray	.010"	.132" Nom.	2" Lay on Cable

# MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius	
Rated -80C to 200C	17.7 lbs/m	10 X OD	

### **ELECTRICAL PROPERTIES**

Max. Operating Voltage

UL Rated 300V Power Ltd.

# INDUSTRY APPROVALS AND COMPLIANCE

#### Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasian, Acid
Applications	Communications, Audio, Control, Instrumentation Remote, Signaling, Power-limited systems
Flame Test	NFPA 262 / FT6
NEC / (UL) Specification	CL2P / CMP
CEC / C (UL) Specification	CMP

#### MISCELLANEOUS

Markings: TYPE CL2P - TYPE CMP 20 AWG (UL), C(UL) FEP/FEP E130356 ROHS

Color Code: Black / Red / White /

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

\* Specification subject to error and may change without notice