



REV.	DESCRIPTION	DATE
0	Initial release.	6/18/2018
General Properties	2 AWG 665/30 BC EXRAD FX Battery Cable	6/18/2018
General Composition of Cable	See Below	<i>[Signature]</i>
		
(Dimensions based upon 15-07493-xxxx) Part Number (preassigned) Color Code 15-08423-002 Red 15-08423-001 Black 15-08423-003 Orange Packaging: 1000ft per 24" wood spool Min length 100ft, up to 3 lengths per spool		
Physical Data		Dimensions (Nom.)
		inches mm
1. Conductor:	2 AWG 665/30 BC	.310" min, .325" Max 0.318 8.08
2. Insulation:	EXRAD FX wall thickness: 42 mil nominal	.363" Min, .405" Max 0.393 9.98
Custom Print Legend	BATTERY CABLE STX XXX AWG SAE J1127 60V DC 150°C (DRY) OIL & GASOLINE RESISTANT CCC XXXXX	
Print Spacing:	every 12 inches	XXX=Awg Size XXXXX=Lot Code Info
Electrical Data	Min. Conductor Area (CMA): 62450	
	Voltage Rating: 60V per SAE J1127	
General Data	Use: Battery Cable	
	Temperature Range: -40° C to +150° C	
Bend Radius:	inches	mm
	1.8	45
	TITLE 2 AWG 665/30 EXRAD FX-Custom Print Legend-Mercury Marine	
UNLESS OTHERWISE SPECIFIED, DIMENSIONS AND TOLERANCES ARE IN INCHES	DRN. Steve Blum	DATE 6/18/2018
	CKD. Sue Tatro	DATE 6/18/2018
DO NOT SCALE THIS DRAWING	SIZE A	PART NUMBER DOCUMENT NUMBER 17228
<small>THIS DRAWING OR ONE DRAWING IS THE PROPRIETARY PROPERTY OF Champlain Cable Corporation, and may not be used, reproduced or disclosed to others, in whole or in part, without written authorization.</small>		PAGE 1 of 1