

## Specification Sheet

Part Number: 151-01528



**Article Number**

151-01528

**Type**

FMB4APT-I

**Color**

White (WH)

**Features & Benefits**

- One base fits more surfaces – flat, curved and moderately angled – for versatile applications.
- High-strength, weather-resistant adhesive offers excellent performance indoors and out.
- 4-way opening allows parallel or perpendicular cable routing options.

**Quantity Per**

bag

**Product Description**

HellermannTyton FlexTack Adhesive Cable Tie Mounts deliver excellent mounting performance on flat, curved and moderately angled surfaces. Use in combination with 18- through 50-pound cable ties to provide stability when securing bundles. Excellent performance in extreme environmental conditions for a wide range of indoor and outdoor applications; on varnished, powder coated, metal or plastic surfaces; in electrical equipment; and where drilling a hole is not possible or desirable. The 4-way saddle allows cable ties to be inserted parallel or perpendicular to the wire bundles.

<b>Short Description</b>	Flexible Cable Tie Mounting Base, 1.1" x 1.1", 0.21" Max Tie Width, PA66HS, White, 100/pkg
<b>Global Part Name</b>	FMB4APT-I-PA66HS-WH
<b>Length L (Imperial)</b>	1.1
<b>Length L (Metric)</b>	28.0
<b>Fixation Method</b>	Self-Adhesive
<b>Width W (Imperial)</b>	1.1
<b>Width W (Metric)</b>	28.0
<b>Height H (Imperial)</b>	0.25
<b>Height H (Metric)</b>	6.3
<b>Cable Tie Width Max (Imperial)</b>	0.213
<b>Cable Tie Width Max (Metric)</b>	5.4
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Adhesive</b>	Acrylate with base of acrylic foam
<b>Flammability</b>	UL 94 V2 (excluding adhesive)

<b>Halogen free</b>	Yes
<b>Adhesive Operating Temperature</b>	-40°F to +194°F (-40°C to +90°C)
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	0.17964
<b>Weight (Imperial)</b>	0.396