



Specification Sheet

Lake Cable Part #: C184(41)/CSA-09/2516

Description: 18 AWG 4 conductors stranded bare copper wire, PVC insulation, unshielded, with an overall pressure extruded PVC jacket.

- 1. Conductor**
 - 1.1. AWG Size & Stranding: 18 AWG 41 Strands Class M
 - 1.2. Material: Annealed Bare Copper
 - 1.3. Conductor Count: 4 Conductors
- 2. Insulation**
 - 2.1. Material: Polyvinylchloride
 - 2.2. Wall Thickness: 0.032"
 - 2.3. Color Code: White, Black, Orange, Red
- 3. Cable Assembly**
 - 3.1. Cable Lay Length: 4.50" LHL (2.6 Tw/Ft) Nominal
 - 3.2. Separator: Tissue Paper - 100% Coverage
- 4. Jacket**
 - 4.1. Material: Pressure Extruded Polyvinylchloride
 - 4.2. Wall Thickness: 0.049"
 - 4.3. Diameter: 0.370" ± 0.008"
 - 4.4. Color: White
 - 4.5. Ripcord: N/A
 - 4.6. Weight: 84 Lbs/Mft
 - 4.7. Convolution Standard: Level 2
- 5. Markings**
 - 5.1. Type: Cable permanently identified via surface inkjet print
 - 5.2. Legend: E206787 18AWG 4C 9U AWM 2516 600V 105°C OR CSA LL226471 AWM I/II A/B 105°C 600V FT1 FT2 "ROHS COMPLIANT" MADE IN USA
 - 5.3. Footage Markers: N/A
- 6. Standards**
 - 6.1. UL recognized component AWM Style 2516 per UL 758 for external interconnection
 - 6.2. CSA component AWM I/II A/B per CSA Standard C22.2 No. 210-11
 - 6.3. Maximum Operating Voltage: 600V RMS
 - 6.4. Cable is RoHS III compliant per Directive 2015/863/EU
 - 6.5. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated July, 7 2017
 - 6.6. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

Date

SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION