

# MULTICONDUCTOR CABLE

MULTICONDUCTOR  
OVERALL FOIL SHIELD

300V - 24 GAUGE



## Description:

Each Conductor Tinned Copper, Color Coded Polyvinylchloride Insulation, Conductors Cabled. Overall Mylar Supported Aluminum Foil Shield, Stranded 24 Gauge Tinned Copper Drain Wire, Gray Polyvinylchloride Jacket Overall.

## Specifications:

UL Listed, NEC Type CM, 75°C  
UL AWM Style 2464, 80°C, 300V  
CSA Certified PCC FT-4

WEICO NO.	NO. OF CONDUCTORS	COLOR CODE	NOM. JACKET THICK. (INCHES)	NOM. O.D. (IN)
#24 - Stranded (7/32) Nom. Ins. Thickness .010"				
7503	3	D	.035	.168
7504	4	D	.035	.190
7505	5	D	.035	.195
7506	6	D	.035	.215
7507	7	D	.035	.215
7508	8	D	.035	.220
7509	9	D	.035	.250
7510	10	D	.035	.250
7515	15	E	.035	.280
7520	20	E	.035	.320
7525	25	E	.040	.360

WEICO NO.	NO. OF CONDUCTORS	COLOR CODE	NOM. JACKET THICK. (INCHES)	NOM. O.D. (IN)
7530	30	E	.040	.380
7540	40	E	.040	.430
7550	50	E	.045	.490

**Standard Put-Ups: 100 ft., 500 ft., 1000 ft.**