

18 AWG 2 Stranded Conductors Shielded Plenum/FT6

Part Number: 3214

Ratings	CMP, CL3P, FPLP, FT6
Approvals	ETL Listed

Construction

Conductor Type	18 AWG 19 Strand Bare Copper
Conductor Count	2
Insulation Colors	Black, Red
Insulation Type	Plenum PVC
Insulation Thickness	0.007" nom.
Cable Lay Length	2.25" nom.
Shielding	Aluminum Foil/Mylar
Rip Cord	Yes
Jacket Material	Plenum PVC
Jacket Thickness	0.015" nom.
Overall Outer Diameter	0.156" nom.
Flame Rating	NFPA 262 (Plenum); CSA C22.2 No. 2556 (FT6)
Print Legend	HONEYWELL P/N 3214 2C 18AWG SHIELDED 3038058 (ETL) CL3P OR FPLP OR CMP C(ETL)US FT6 75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

Electrical & Environmental

Temperature	-20°C to 75°C
Voltage	300V max.
Capacitance	59.3 pF/ft. nom.
Impedance	31 Ohms nom.
DC Resistance	6.66 Ohms/1000' at 20°C
RoHS Compliant	Yes