

18 AWG 6 Stranded Conductors Riser/FT4

Part Number: 2116

Ratings CMR, CL3R, FPLR, FT4, Sunlight Resistant
Approvals ETL Listed

Construction

Conductor Type 18 AWG 19 Strand Bare Copper
Conductor Count 6
Insulation Colors Black, Red, White, Green, Brown, Blue
Insulation Type Polypropylene
Insulation Thickness 0.006" nom.
Cable Lay Length 5.50" nom.
Shielding
Rip Cord Yes
Jacket Material PVC
Jacket Thickness 0.017" nom.
Overall Outer Diameter 0.208" nom.
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
Print Legend HONEYWELL P/N 2116 6C 18AWG 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4 SUN RES
75C (RoHS) W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

Electrical & Environmental

Temperature -20°C to 75°C
Voltage 300V max.
Capacitance 22.7 pF/ft. nom.
Impedance 67 Ohms nom.
DC Resistance 6.66 Ohms/1000' at 20°C
RoHS Compliant Yes