



PINOUT		
RJ45S		RJ45S
CASE	DRAIN	CASE
1	WH/OR	1
2	OR/WH	2
3	WH/GN	3
4	BL/WH	4
5	WH/BL	5
6	GN/WH	6
7	WH/BR	7
8	BR/WH	8

PRODUCT INFORMATION:

- 1.) 24AWG STRANDED TINNED COPPER CONDUCTORS
- 2.) OVERALL FOIL & BRAID 600V AWM RATED
- 3.) SHIELDED 8X8 MOD PLUGS INSTALLED EACH END
- 4.) ALUMINUM/POLYESTER SHIELD WITH A 24AWG STRANDED TINNED COPPER DRAIN WIRE
- 5.) INDUSTRIAL GRADE HIGH FLEX SUNLIGHT RESISTANT, THERMOPLASTIC ELASTOMER TEAL JACKET CMX OUTDOOR – CM
- 6.) OPERATING TEMP RANGE -40°C TO +80°C
- 7.) BLACK STRAIN RELIEF BOOTS INSTALLED ON EACH END



FILE NAME
CONTRACT NO N/A
DRAWN 11/13/17 JOELH
CHECK 11/13/17 JOSHW
APPR. 11/13/17 JOSHW
ISSUED 11/13/17 JOELH

CUSTOMER SPEC			
C284989			
RJ45S/45S 5E TEAL 600V			
SIZE	FSCM NO	DWG NO	REV
C		C284989	A
SCALE	1'0"=1'0"	WEIGHT	N/A
SHEET	1 OF 1		