

THERM-O-LINK INC.

10513 Freedom Street
GARRETTSVILLE, OHIO 44231

(330) 527-2124
FAX: (330) 527-2123

Material Specification

Customer: IEWC

TOL Part Number: 1569-20-7-T
Spec Revision Level: A8

Description: 20 GA AWM UL 1569/1007, PVC 105 DEGC 300V
VW-1, 7 STRANDS TINNED

Conductor (Stranding): 7 x .0126" Tinned Copper, UL
Conductor OD (Nom) 0.038 inches
Max. Lay Length: 1.0 inch Lay
Min Avg Wall Thickness: 0.015 inches
Min O. D: 0.069 inches
Nom. O. D: 0.072 inches
Max Runout: 0.006 inches
Circular Mils (CMA): 926 (Min)
Surface Print: 20 AWG RU AWM STYLE 1569 OR STYLE 1007
E73051 105C 300V VW-1 CSA TR-64 90C FT1 LL 55994

This Product is RoHS Compliant.

Specification Reference Data

SAE: N/A Ford: N/A Chrysler: N/A
UL : AWM 1569/ 1007/STD 758 /1581 CSA: C22.2 # 127-2009
Packard: N/A
Other:

Therm-O-Link, Inc. certifies that the above specifications are met or exceeded in the production of this product.

Verified By: Mir Hussain (Corporate Product Engineering Manager)

Date: 7-20-2018