



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
bhanlon@huesonwire.com

Issue Date: 6/11/2018

Issue: 1

Construction

Description: 3/C 26 19/38 TC TPE/PUR OAFS + Braid		Diam. (In)
Component:	3 Conductors	
Conductor:	26 AWG 19/38 Tinned Copper to ASTM B-8	0.02"
Insulation:	0.01" TPE Insulation	0.04"
Color Code:	Black + Red + Color to be determined	0.04"
Cable Assembly:	3 Conductors Cabled	0.086"
Fillers	No Fillers Required	0.086"
Drain Wire:	26 AWG 19/38 Tinned Copper (Drain Wire In)	0.086"
Shield:	Aluminum Mylar Tape (Foil Side In)	0.089"
Separator:	Clear Mylar Tape (25% Overlap)	0.089"
Braid:	Tinned Copper Braid Shield 95% Coverage	0.111"
Jacket:	0.04" Polyurethane	0.190"
Jacket Color:	Red	0.190"

Print: www.schmitt-inc.com

Specifications: Temp Voltage Flame
UL
 Canadian cRU

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ180281