

## Specification Sheet

Lake Cable Part #: C264CT/X-2464

**Description:** 26 AWG 4 conductors 7 strands tinned copper wire, PVC insulation, unshielded, with an overall

PVC jacket.

1. Conductor

1.1. AWG Size & Stranding: 26 AWG 7 Strands Class B 1.2. Material: Annealed Tinned Copper

1.3. Conductor Count: 4 Conductors

2. Insulation

2.1. Material: Polyvinylchloride

2.2. Wall Thickness: 0.010"

2.3. Color Code: Red, Yellow, White, Black

3. Assembly

3.1. Nominal Lay Length: 1.50" LHL (8.00 tw/ft)

4. Jacket

4.1. Material: Polyvinylchloride

4.2. Wall thickness: 0.032"
4.3. Diameter: 0.156"
4.4. Color: Black
4.5. Ripcord: Yes
4.6. Weight: 14 Lbs/Mft

5. Markings

5.1. Type: Cable permanently identified via surface inkjet print

5.2. Legend: LAKE CABLE E206787 26AWG 4C 9U AWM 2464 300V 80°C "ROHS COMPLIANT"

MADE IN USA

5.3. Footage Markers: Yes

6. Standards

6.1. For external interconnection or internal wiring

6.2. UL recognized component as type AWM 2464 per UL standard 758

6.3. Cable is RoHS III compliant per Directive 2015/863/EU

6.4. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated July, 7 2017

6.5. Maximum Operating Voltage: 300V RMS

6.6. Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION

you have read and agreed to this specification sheet and upon confirmation of your order; this
item may be non-cancelable and
non-returnable.
non-recurriable.
-
Signature
Company