

## Specification Sheet

## Lake Cable Part #: SVT125S/M3E2-ER

Description: 12 AWG 5 conductor 7 strand bare copper with polyvinylchloride and nylon insulation an

aluminum/mylar shield with a tinned copper drain wire and overall PVC jacket 600V tray cable,

approved for use in SUN RES DIR BUR OIL RES I & II 90°C applications.

1. Conductor

1.1. AWG Size & Stranding: 12 AWG 7 Strands Class B 1.2. Material:

Annealed Bare Copper

1.3. Conductor Count: 5 Conductors

2. Insulation

2.1. Material: Polyvinylchloride & Nylon
2.2. Wall Thickness: 0.015" PVC & 0.005" Nylon
2.3. Color Code: Method 1, Table E-2 & numbered

3. Assembly

3.1. Lay Length: 5.25" LHL 3.2. Fillers: N/A 3.3. Binder: N/A

3.4. Shield: Aluminum/Mylar Tape - 100% Coverage

3.5. Drain Wire: 16 AWG 7 Strands Tinned Copper

4. Jacket

4.1. Material: Polyvinylchloride

4.2. Wall Thickness: 0.045"

4.3. Diameter: 0.447" ± 0.035"

4.4. Color: Black 4.5. Ripcord: Yes

4.6. Weight: 172 lbs./Mft.

5. Markings

5.1. Type: Cable shall be permanently identified via surface inkjet print

5.2. Legend: LAKE CABLE E208309 12AWG 5C SHIELDED (UL) TC-ER THWN-2/VW-1 600V 90°C

DRY/WET PVC JACKET SUN RES DIR BUR OIL RES I & II FT4 "ROHS

COMPLIANT" MADE IN USA

5.3. Footage Markers: Yes

6. Standards

- 6.1. Refer to NEC (NFPA 70) article 336 for installation guidelines
- 6.2. Cable is suitable for use in Class I Division 2 hazardous locations
- 6.3. UL listed as Type TC-ER per UL Standard 1277 for tray cables
- 6.4. UL approved for Direct Burial, Sunlight and Oil I & II Resistant applications
- 6.5. Individual conductors pass UL VW-1 flame test, rated THWN-2/VW-1
- 6.6. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
- 6.7. Cable is RoHS III compliant per Directive 2015/863/EU
- 6.8. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated July, 7 2017
- 6.9. Made in the USA

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION

Your signature constitutes that you have read and agreed to this
specification sheet and upon
confirmation of your order; this item may be non-cancelable and
non-returnable.
Signature
Company

Date