



Route 9, P.O. Box 1180
West Brookfield, MA 01585
(508) 867-3155
(508) 867-7767
(508) 867-7768
Fax: (508) 867-5132

COMMERCIAL SPEC: WCT-5165

GENERAL DESCRIPTION: TWO CONDUCTOR SPECIAL DIAMETER SHIELDED CABLE

INNER CONDUCTORS: 26 AWG, 19X38 SILVER PLATED COPPER
40 MICRO INCH MINIMUM SILVER PLATING

O.D. TOLERANCE: .0181" TO .0193"

PRIMARY DIELECTRIC INSULATION: EXTRUDED PTFE TEFLON

COLORS: Yellow and white

O.D. TOLERANCE: .029" AND .035"

CABLING: TWO CONDUCTORS TWISTED 1 1/4" LEFT HAND LAY

O.D. TOLERANCE: N/A

SHIELD DESCRIPTION: 40 AWG SILVER PLATED COPPER - 85% - 90% COVERAGE

JACKET DESCRIPTION: .008" WRAPPED PTFE TEFLON TAPE - COLOR Yellow

FINAL DIAMETER: .100" MAXIMUM

ADDITIONAL NOTES, IF ANY:

SPARK TEST: 2900 VAC

DIELECTRIC TEST INNERS: 1500 VAC

RATED: 300 VAC, 200 C

WCT-5165
04-20-05

