

LUTZE TOP-T Locknuts Metal

Metal Locknuts for use with NPT, PG, Metric and EMC Fittings



Characteristics

- Hexagonal locknut for secure tightening of cable fittings and accessories
- Temperature range up to +200°C/+392°F

Locknut Specifications

Material Brass, nickel plated

Part No.	For Thread Type	OD - Ø mm	SW mm	H mm
NPT				
LMNPT38	NPT 3/8"	26.5	24	5
LMNPT12	NPT 1/2"	26.5	24	5
LMNPT34	NPT 3/4"	37.5	34	6
LMNPT10	NPT 1"	46.4	42	6
LMNPT1014	NPT 1¼"	57.4	52	7
LMNPT1012	NPT 1½"	65.1	60	7
LMNPT20	NPT 2"	81.8	74	8
LMNPT2012	NPT 2 ½"	89	80	10
LMNPT30	NPT 3"	105.5	95	10
PG				
LMPG7	PG 7	16.6	15	2.8
LMPG9	PG 9	20	18	2.8
LMPG11	PG 11	23.5	21	3
LMPG13	PG 13.5	25.5	23	3
LMPG16	PG 16	29	26	3
LMPG21	PG 21	35.5	32	3.5
LMPG29	PG 29	45	41	4
LMPG36	PG 36	56	51	5
LMPG42	PG 42	66	60	5
LMPG48	PG 48	70.5	64	5.5
METRIC				
LMM12	M12x1.5	16.6	15	2.8
LMM16	M16x1.5	21	19	3
LMM20	M20x1.5	26.5	24	3.5
LMM25	M25x1.5	33	30	4
LMM32	M32x1.5	39.5	36	5
LMM40	M40x1.5	51	46	5
LMM50	M50x1.5	66	60	5
LMM63	M63x1.5	77	70	6
LMM75	M75x1.5	89	80	7
LMM90	M90x1.5	112	100	8
EMC - METRIC CUTTING TEETH				
LMM12-C	M12x1.5	16.5	15	3.3
LMM16-C	M16x1.5	21	19	3.5
LMM20-C	M20x1.5	26.5	24	3.5
LMM25-C	M25x1.5	33	30	3.5
LMM32-C	M32x1.5	39.5	36	4
LMM40-C	M40x1.5	51	46	4.6
LMM50-C	M50x1.5	66	60	5.6

EMC Metric Locknuts with Cutting Teeth

- For secure tightening of EMC cable fittings
- To cut through paint layers or powder coatings ensuring optimal contact
- Increased vibration resistance

Specifications are subject to change without prior notice