



TE Wire & Cable

The most trusted name in thermocouple wire since 1941

107 North Fifth Street • Saddle Brook, NJ 07663-6167 • 888-4TE-WIRE • www.tewire.com

PRODUCT SPECIFICATION: FW15357

16 AWG, 2-pair, type SX/BX thcpl extn cable, fiberglass ins and jkt, SS braid

Prepared by: M. PETERS
Date: 2/19/2018

Revision A

Manufacturing description: TFG/GSK-16-2CU,2SXN

Customer Part Number: CM-RSX-004

Construction Details

Conductor 16 AWG, Solid thermocouple type S and B extension per ASTM E230 & ANSI MC96.1

Insulation Helically wrapped PTFE tape and braided fiberglass yarn.
Color: Cu (1)Black, (1)White with black tracer; SXN (1)Red (1)White with red tracer
Braided fiberglass yarn over the teflon tape.

Cabling (4) Insulated conductors are twisted together.
Mylar bedding tape to bind conductors together.

Jacket Fiberglass jacket over the mylar bedding.
Saturant Color: None

Braid Stainless steel overbraid over the jacket. Nominal optical coverage 85%
Nominal Final Diameter: .256"

The information contained in this drawing is proprietary property of
TE Wire and cable. It may not be used or reproduced, in whole or in part,
without written authorization of TE Wire and Cable