



Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372

bhanlon@huesonwire.com

C5904

Issue Date: 3/13/2020

Construction

IEWC P/N: 32074058

Issue: 1

Description:	4/C 22 7/30 BC PVC/PVC OAFS + Drain	Diam. (In)
Component:	4 Conductors	
Conductor:	22 AWG 7/30 Bare Copper to ASTM B-8	0.030"
Insulation:	0.01" Premium Grade PVC Insulation	0.050"
Color Code:	Brown, Blue, Black, Green/Yellow	0.050"
Cable Assembly:	4 Conductors Cabled	0.121"
Drain Wire:	22 7/30 TC Drain Wire In	0.121"
Shield:	Aluminum Mylar Tape Foil Side in	0.124"
Jacket:	0.04" Matte Finish PVC	0.204"
Jacket Color:	Black	0.204"

Print: E174416 RU AWM 2464 80C 300V VW-1 --- cRU AWM I/II A/B 80C 300V FT1 W1196 22/4

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
UL	AWM-2464	80°C	300	VW-1
Canadian cRU	AWM	80°C	300	FT-1 I/II A/B

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ180420