



Description: Six 24 AWG Conductors,
 Overall Foil Shield and
 TPE Jacket

Date: 08/17/18

JM Part Number: TBD
Reference: TBD

Components Six 24 AWG Insulated Conductors

Conductor: 24 AWG, 7/32 tinned copper

Insulation: .016" nominal wall of TPE (see color code) .056"

Overall Cable Construction

Cabling: Six conductors with FR PP Fillers as needed for roundness

Binder: Fleece tape

Drain Wire: 24 AWG, 7/32 tinned copper

Foil Shield: Aluminum-Mylar tape, Aluminum side IN

Ripcord: Nylon under jacket

Jacket: .042 nominal wall of Black TPE .260"

Print (White Inkjet)

E66440 AWM 20237 125C 300V --- LL41103 CSA AWM I/II A/B 125C 300V FT1

Color Code

- | | |
|-----------|----------|
| 1. Orange | 4. Blue |
| 2. Green | 5. Black |
| 3. Brown | 6. White |

Requirements

Temperature: 125°C	Approvals: UL AWM Style 20237
Voltage: 300V	CSA AWM, FT1
	Materials are RoHS Compliant
	(201165/EU & EU 2015/863)
Capacitance: 15 pF/ft (Between Conductors)	
Inductance: .167 µH/ft	

Written By:	rac	08/17/18	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				