





UPC Code: 07847751565

Country Of Origin: United States

NEMA: L1-15P



7545-C

15 Amp, 125 Volt, NEMA L1-15P, 2P, 2W, Plug, Locking Blade, Industrial Grade, Non-Grounding - BLACK-WHITE

Leviton's Industrial Grade Locking Devices are built to provide unparalleled quality and superior performance in the most severe industrial settings. Leviton combines the best materials available with superior production standards to produce a broad selection of Locking Devices of unmatched flexibility and dependability.

Technical Information

AC Horsepower Ratings
Horsepower Rating: 1/2 HP

Electrical Specifications

Grounding: Non-Grounding

Amperage: 15 A Voltage: 125 VAC

Pole: 2 Wire: 2

Dielectric Voltage: Withstands 2000V

per UL498

Current Interrupting: Certified for current interrupting at full rated current

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Environmental Specifications

Flammability: Rated HB or better UL94 Operating Temperature: -40°C to 60°C

Environment: Dry

Material Specifications

Body Material: Impact Modified Nylon

Back Cover: Thermoplastic

Wire Module: Nylon Cord-Clamp: Nylon Clamp Insert: Nylon Blades/Contacts: Solid Brass Terminal Screws: Brass

Assembly Screws: Steel, Zinc Plated

Color: Black-White

Mechanical Specifications

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Terminal Accom.: 18-10 AWG
Product ID: Ratings are permanently

marked on device

Cord Range: .240 - .700 Wire Gauge: 18-10 AWG

Product Features

NEMA: L1-15P

Color: Black-White

Brand: Black and White


Standards and Certifications


NEMA: WD-6 ANSI: C-73

UL Fed Spec WC-596: File E13393 **CSA C22.2 No. 42**: File LR-406

NOM Certified: 057

Warranty: Lifetime Warranty





SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

