

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 830667

DESCRIPTION: 14/2 & 18/12 STRANDED SOOW CONTROL CABLE

CONSTRUCTION: This cable consists of two 14 AWG and twelve 18 AWG bare copper insulated conductors cabled with fillers

and an overall jacket.

APPLICATION: UL Subject 62; CSA C22.2 No. 49; NEC Article 400

600V Portable Oil and Water Resistant Submersible Outdoor Flexible Power Cable APPROVALS:

14 AWG

Construction Parameters:

Conductor 14 AWG Bare Copper

18 AWG Bare Copper 41/30

Stranding 18 AWG 16/30 Insulation Material **EPDM**

Insulation Thickness 14 AWG 0.046" Nom. 0.031" Nom. 18 AWG

Insulated Conductor Diameter 14 AWG 0.166" Nom. 0.108" Nom. 18 AWG

Number of Conductors 14 AWG 18 AWG 12

7.50" Nom. Lay Length Filler Type Polypropylene Paper Tissue Separator/Wrap Jacket Material CPE

0.106" Nom. Jacket Thickness 0.760" Nom. Overall Cable Diameter +/- 0.005" Approximate Cable Weight 319.6 Lbs/1M' Nom.

Flame Rating **UL/CSA Horizontal Flame Test**

Electrical Properties:

-40°C to 90°C Temperature Rating 600 V RMS Max. Operating Voltage DC Resistance per 14 AWG Conductor @ 20°C 2.53 Ohms/1M' Nom. DC Resistance per 18 AWG Conductor @ 20°C 6.49 Ohms/1M' Nom.

Insulation Colors 14 AWG Center Conductors from Top: Purple Black

> **18 AWG** Outer Conductors from Top, Clockwise: Orange Brown Yellow Green Black/White

Red/White Red Blue/White Blue Tan/White Tan Orange/White

Jacket Color Black

Legend (White Surface Ink Print) CCI 14 AWG (2.08mm²) 2/C & 18 AWG (0.82mm²) 12/C SOOW E54864-L (UL) 600V -40C

TO 90C -- CSA LL39753(L) SOOW 600V -40C TO 90C FT2 P-07-KA070018-1 MSHA

(Julian Date)

Complies with EU Dir. 2011/65/Eu (RoHS-2)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.

Customer Name	 	
Customer Approval _	 	

Specification Issue Date: July 29, 2013