



ALPHA WIRE

Part Number: 18-2344

Issue: C

Page 1 of 1 Pages

Issue Date:

10/12/2018

Cable Specification

Component 1 2 COND

Conductor: 18 (16/30) AWG TC

Insulation: 0.032" Wall, Nom. PVC

 Color Code: 2 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED

Final Assembly 2 Components

 Core Wrap: NWP Tape, 25% Overlap, Min.

Shield: AM Foil Tape, 25% Overlap, Min.

 Drain Wire: 18 (16/30) AWG TC

 Braid: TC,85% Coverage, Min.

Jacket: 0.033" Wall, Nom., PVC

 Jacket OD: 0.318"

 Jacket Color: SLATE

Approvals

 UL: AWM/STYLE 1032

 AWM/STYLE 2129

 CSA: NONE

 MIL: NONE

 CE Compliant: YES

 ROHS Compliant: YES

 REACH Compliant: NO

Miscellaneous

 Temperature: 90 C

 Voltage: 1000 V_{RMS}

 Put Ups: 1000 FT PUTUP

 Requested Quantity: 25000Ft.

Application Notes

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.