

ALPHA WIRE

Part Number: 18-2051

Issue:

Page 1 of 1 Pages

Issue Date:

8/3/2018

Cable Specification

Component 1 7 PAIR
Conductor: 24 (10/34) AWG TC
Insulation: 0.010" Wall, Nom. SR-PVC
Color Code: 14 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED
Pair: 2/Cond Cabled Together

Final Assembly 7 Components
Core Wrap: NWP Tape, 25% Overlap, Min.
Shield: FLEXAM Foil Tape, 25% Overlap, Min.
Drain Wire: 26 (7/34) AWG TC
Braid: TC, 85% Coverage, Min.
Jacket: 0.040" Wall, Nom., PVC
Jacket OD: 0.361"
Jacket Color: SLATE
Jacket Separator: TP Tape, 25% Overlap, Min.

Approvals

UL: AWM/STYLE 2661
AWM/STYLE 21894
CM
CSA: c(RU) AWM I/II A/B
c(UL) CMG
FT4
MIL:
CE Compliant: YES
ROHS Compliant: YES
REACH Compliant: YES

Miscellaneous

Temperature: 105 C
Voltage: 300 V_{RMS}
Put Ups: 1000 FT PUTUP
Requested Quantity: 1000Ft., 5000Ft.

Application Notes

Note:

Ten different colors available. May use Dark shaded colors as extra to make 14 solid colors.

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.