

SJTOOW

105°C PVC Cord. 300 Volts. Flexible Copper Conductors. PVC Insulation and Jacket. Rated for Hard-Usage Service Cords. Rated FT2 Flame Resistant.



Image not to scale or color & is for reference only. See Table 1 for Dimensions

CONSTRUCTION:

- Conductors:** Class K, Flexible bunch stranded bare copper per ASTM B3 and B174
Insulation: Polyvinyl Chloride (PVC), Colors: Black, White, Green, Purple, Purple/White
Assembly: The insulated conductors are cabled together with fillers. A tissue paper is helically applied over the assembly to facilitate overall jacket removal.
Jacket: White, PVC

APPLICATIONS AND FEATURES:

Southwire Type SJTOOW Flexible Cords are permitted for use as specified by Article 400 and related articles of the 2017 National Electric Code. Some typical applications for Type SJTOOW Cord include, but are not limited to: Wiring for industrial machinery such as washing machines and other large appliances, heavy-duty portable tools, motors and temporary electrical power.

SPECIFICATIONS:

- ASTM B3, B174
- UL 62 - Type SJTOOW
- CSA C22.2 No. 49 - Type SJTOOW

SAMPLE PRINT LEGEND: (InkJet Print)

(UL) VW-1 E46194 SJTOOW 5/C 18 AWG (0.82mm²) 105C DRY 60C WATER RESISTANT 300V
(CSA) FT1,FT2 LL90458 "RoHS-2 COMPLIANT"

TABLE 1 - WEIGHTS & MEASUREMENTS

Stock Code	Cond. Size (AWG)	No. of Cond.	No. of Strands	Insulation Thickness (mils)	Jacket Thickness (mils)	Nominal OD (mils)	Nominal Weight (Lbs/Mft)
TBD	18	5	16	32	43	380	87

All dimensions are nominal and subject to normal manufacturing tolerances



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2016 Southwire Company, LLC. All Rights Reserved

