


TECHNICAL DATA SHEET

Cable Diagram



| Description | |
|----------------------------|-----------------------|
| Cable Part Code* | TBA |
| Cable Description | 24AWG XLP Hookup wire |
| Cable References Standards | UL AWM 3302 |

| Conductor | |
|--------------------|------------------------|
| Conductor Material | Stranded Tinned Copper |
| Conductor Size | 24AWG |

| Insulation | |
|-------------------------------|-----------|
| No. of Cores / Pairs / Triads | 1 Cores |
| Insulation Material | XLP(LSZH) |
| Nom. Insulation Diameter (mm) | 1.0 |

| Physical/Mechanical Properties | |
|--------------------------------|-----------------|
| Temperature Rating (°C) | -20 to + 105°C |
| Oil Resistance | Yes |
| UV Resistance | Yes |
| Flame / Fire Retardancy | IEC 60332-1/FT2 |
| Nom. Cable Weight(kg/km) | 2.7 |

| Electrical Properties | |
|---|------|
| Voltage Rating (V) | 30 |
| Max. Conductor Resistance @ 20°C (Ω/km) | 94.2 |

*Ordering stock code will be created at the time of placing the order and the stock code will include cable part code, outer jacket color & putup length.

SZ-CA-0819

© 2018 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.