

Description: Three Conductor 20 AWG,
Overall PVC Jacket

Create Date: 01/08/2019

JM Part No: TBD

Reference: 203C/X1-00RAM

Components	Three 20 AWG, SRPVC Insulated Conductors	<u>Nom OD</u>
	Conductor: 20 AWG, 7/.0121 bare copper	
	Insulation: .010" nominal wall of SRPVC (see color code)	.056"

Overall Cable Construction

Cabling: 3 conductors cabled together
 Jacket: .025" nominal wall of Black PVC .171"

Print White Inkjet Every 24"
 E67179 3/C 20 AWG 75C (UL) CL3R SUN RES OR C(UL)US CMR FT4 ROHS COMPLIANT
 MADE IN USA
 [Sequential Footage Marking]

Color Code

- | | |
|----------|-----------|
| 1. Black | 3. Yellow |
| 2. White | |

Requirements

Temperature: 75°C
 Voltage: 300 V
 Cable Weight: 19 lbs/Mft
 Copper Weight: 9.4 lbs/Mft

Approvals:
 UL CL3R
 UL CMR
 cUL CMR FT4
 Sunlight Resistant
 Materials are RoHS Compliant
 (2011/65/EU & EU 2015/863)

Written By:	ka/ba	01/08/2019	Rev. 0	Initial Issue
Revised By:				
Revised By:				