



Manufactured By:
 134 Ferry St.
 South Grafton, Ma 01560
 www.huesonwire.com

Issue Date: 12/4/2019

Issue: 1

Construction

Description: 4/C 20 10/30 PP/PUR OAFS + Drain		Diam. (In)
Component:	4 Conductors	
Conductor:	20 AWG 10/30 Tinned Copper to ASTM B-174	0.036"
Insulation:	0.01" Polypropylene 0.056" +/- .003"	0.056"
Color Code:	Black, White, Red, Green	0.056"
Cable Assembly:	Bunch Cable 4 Conductors	0.136"
Drain Wire:	20 10/30 TC	0.136"
Shield:	Aluminum Mylar Tape Foil In	0.140"
Separator:	Paper Tape	0.144"
Jacket:	0.105" Polyurethane	0.350"
Jacket Color:	Black 0.350" +/- 0.010"	0.350"

Print: DSC P/N: 611A200 REV B ROHS 20 AWG

Specifications: AWM Style Temp Voltage Flame

UL

Canadian cRU

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ-190457



Issue Date: 12/4/2019
Issue: 1

Drawing/Rotation:

