


TECHNICAL DATA SHEET

Diagram



Description	
Cable Part Code*	I535WKA10
Cable Type	10P1.5 mm ² XLP/IS/OS/LSZH/SWA/LSZH
Cable References Standards	BS EN 50288-7, IEC 60332-3A, IEC 60332-1-2

Conductor	
Conductor Material	Bare Copper
Conductor Size	1.5 mm ²
Conductor Stranding Standard	IEC 60228-Class-2

Insulation	
No. of Cores/Pair/Triad/Quad	10 Pairs
Insulation Material	XLP
Nom. Insulation Diameter(mm)	2.5
Insulation Color Code	Black*White, All cores with number coding 1~10

Shielding	
Shielded/Unshielded	Individual & overall foil Shield with TC drain Wire+Tinned copper braid

Inner Jacket/Sheath Material	
Inner Jacket Material	LSZH
Nom. Diameter Over Inner Jacket (mm)	22.7
Inner Jacket Color	Black

Armoring	
Type of Armor	Galvanized Steel wire Armour
Nom. Diameter Over Steel Wire (mm)	25.2

Outer Jacket/Sheath Material	
Outer Jacket Material	LSZH
Nom. Overall Diameter(mm)	28.7

Physical/Mechanical Properties	
Temperature Rating	-30~90°C
Oil Resistance	Yes
UV Resistance	Yes
Fire Retardant	IEC 60332-3A
Min. Bending Radius	10 X OD
Nom. Cable Weight (Kg/km)	1374

Electrical Properties	
Voltage Rating (V)	300V
Max. Conductor Resistance @20°C	12.34
Max Mutual Capacitance Core to Core @1KHz	150
Max. Inductance to Resistance Ratio L/R	40

*Ordering stock code will be created at the time of placing the order and the stock code will include cable part code, outer jacket color & putup length.

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.