

LUTZE Electronic PLTC PVC, Unshielded

Flexible Electronic Cable with UL/CE/PLTC Approvals



Application

- Multi-conductor industrial grade PLTC electronic cable
- Machine tools, machine and plant construction, HVAC technology, assembly and production lines, process instrumentation and controls
- Compliant with NFPA 79 requirements
- PLTC for installation in cable trays

Characteristics

- Flexible for easy installation
- Easy strip design
- Color coded conductors
- Specially formulated jacket for oil resistance
- Premium durability
- Extended temperature range
- **UL listed** and **NFPA 79** compliant
- Gas/vapor-tight sheath per UL 13
- Talc and Silicone free

Technical Data

Voltage	300V
Temperature	-40°C - +105°C
Minimum bending radius	4 x cable OD
Conductor marking	See tables
Burning behavior	Flame retardant per UL VW-1, FT4
Oil resistance	Oil Res II
Approvals	UL Type PLTC UL Type CM AWM Style 2464 AWM II A/B CE Meets NEC 392, 725, 800 Class I & II, Div. 2 and Class I Zone 2 per NEC 501, 502, 505 (PLTC Use Only) UL 13 RoHS, REACH

Construction

- AWG conductor
- Flexible fine wire stranded tinned copper conductors
- SR-PVC insulation
- Oil resistant premium PVC jacket
- Gray jacket similar to RAL 7001

Specifications are subject to change without prior notice

Part No.	Description No. of conductors	OD / Ø ca. mm	OD / Ø inches	Weight Lbs/Mft	Copper Lbs/Mft
AWG 22 (19/34)					
A3032202	AWG22/2C	4.4	0.173	17	4
A3032203	AWG22/3C	4.6	0.181	21	7
A3032204	AWG22/4C	4.9	0.194	26	9
A3032206	AWG22/6C	5.7	0.223	33	14
A3032208	AWG22/8C	6.2	0.243	42	19
A3032210	AWG22/10C	7.2	0.283	53	24
A3032215	AWG22/15C	8.1	0.318	70	35
A3032220	AWG22/20C	9.0	0.353	90	47
A3032225	AWG22/25C	10.3	0.407	117	59
AWG 20 (19/32)					
A3032002	AWG20/2C	5.0	0.195	21	7
A3032003	AWG20/3C	5.2	0.204	27	11
A3032004	AWG20/4C	5.6	0.220	33	15
A3032006	AWG20/6C	6.5	0.254	45	22
A3032008	AWG20/8C	7.2	0.282	58	30
A3032010	AWG20/10C	8.2	0.323	72	37
A3032015	AWG20/15C	9.2	0.364	99	56
A3032020	AWG20/20C	10.7	0.420	134	75
A3032025	AWG20/25C	11.7	0.461	163	94
AWG 18 (19/30)					
A3031802	AWG18/2C	5.4	0.213	27	12
A3031803	AWG18/3C	5.7	0.223	35	18
A3031804	AWG18/4C	6.1	0.242	43	24
A3031806	AWG18/6C	7.4	0.291	63	36
A3031808	AWG18/8C	7.9	0.312	79	49
A3031810	AWG18/10C	9.1	0.359	97	61
A3031815	AWG18/15C	10.8	0.427	145	91
A3031820	AWG18/20C	11.9	0.468	185	121
A3031825	AWG18/25C	13.1	0.515	226	152
AWG16 (26/30)					
A3031602	AWG16/2C	6.5	0.257	36	16
A3031603	AWG16/3C	6.9	0.271	48	24
A3031604	AWG16/4C	7.7	0.304	62	32
A3031606	AWG16/6C	9.1	0.357	89	49
A3031608	AWG16/8C	10.3	0.407	119	65
A3031610	AWG16/10C	11.9	0.469	149	81
A3031615	AWG16/15C	13.5	0.532	207	122
A3031620	AWG16/20C	14.9	0.587	264	163
A3031625	AWG16/25C	17.0	0.669	336	204

Color Code Table AWG 22

1- BK	13- WH/RD
2- BN	14- WH/OG
3- RD	15- WH/YE
4- OG	16- WH/GN
5- YE	17- WH/BU
6- GN	18- WH/VT
7- BU	19- WH/GY
8- VT	20- WH/BK/BN
9- GY	21- WH/BK/RD
10- WH	22- WH/BK/OG
11- WH/BK	23- WH/BK/YE
12- WH/BN	24- WH/BK/GN
	25- WH/BK/BU

Color Code Table AWG 20, 18 & 16

1- BK	13- RD/GN
2- RD	14- RD/YE
3- WH	15- RD/BK
4- GN	16- WH/BK
5- OG	17- WH/RD
6- BU	18- WH/GN
7- BN	19- WH/YE
8- YE	20- WH/BU
9- VT	21- WH/BN
10- GY	22- WH/OG
11- PK	23- WH/GY
12- TN	24- WH/VT
	25- WH/BK/RD