

Description: Ten Conductor 18 AWG,
 Overall Braid Shield,
 PVC Jacket

Create Date: 02/22/2019

JM Part No: TBD

Reference: 3410

Components	Ten 18 AWG, PVC Insulated Conductors	<u>Nom OD</u>
	Conductor: 18 AWG, 19/30 tinned copper	
	Insulation: .016" nominal wall of PVC (see color code)	.080"

Overall Cable Construction

Cabling: 10 conductors cabled together
 Binder: Clear Mylar tape
 Braid Shield: 36 AWG tinned copper braid, 90% coverage
 Jacket: .035" nominal wall of Gray PVC .413"

Print

Unprinted

Color Code

- | | |
|-----------|------------------|
| 1. Black | 6. Blue |
| 2. White | 7. White/Black |
| 3. Red | 8. Red/Black |
| 4. Green | 9. Green/Black |
| 5. Orange | 10. Orange/Black |

Requirements

Temperature: 105°C
 Voltage: 1000 V
 Cable Weight: 126 lbs/Mft
 Copper Weight: 81 lbs/Mft

Approvals:

Materials are RoHS Compliant
 (2011/65/EU & EU 2015/863)

Written By:	ka/ba	02/22/2019	Rev. 0	Initial Issue
Revised By:				
Revised By:				