

Specification Sheet

Lake Cable Part #: P102C(65)-IEWC

Description: 10 AWG 2 conductor 65 strand bare copper wire, plenum rated PVC insulation, unshielded, with

an overall plenum rated PVC jacket

1. Conductor

1.1. AWG Size & Stranding: 10 AWG 65 Strands1.2. Material: Annealed Bare Copper

1.3. Conductor Count: 2 Conductors

2. Insulation

2.1. Material: Plenum Rated Polyvinylchloride

2.2. Wall Thickness: 0.009"2.3. Color Code: Black, White

3. Assembly

3.1. Nominal Lay Length: 4.25" LHL (2.82 Tw/Ft)

4. Jacket

4.1. Material: Plenum Rated Polyvinylchloride

4.2. Wall Thickness: 0.015"
4.3. Diameter: 0.304"
4.4. Color: White
4.5. Ripcord: Yes

4.6. Weight: 83 Lbs/Mft

5. Markings

5.1. Type: Cable shall be permanently identified via surface inkjet print
5.2. Legend: IEWC E171202 10AWG 2C 75C (UL) CL2P OR C(UL)US CMP
"FOR AUDIO ONLY" FT6 "ROHS COMPLIANT" MADE IN USA

5.3. Footage Markers: Yes

6. Standards

- 6.1. Cable suitable for installation under NEC (NFPA 70) article 800 guidelines
- 6.2. Cable suitable for installation in Canada under Section 60 of CEC, Part I
- 6.3. UL listed as type CL2P per UL standard 13 and as type CMP per UL standard 444
- 6.4. Cable meets NFPA 262 (Steiner tunnel) flame test
- 6.5. Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive
- 6.6. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated June, 27 2018
- 6.7. Made in the USA
- 6.8. AWARNING: This product contains chemicals, including lead, known to the state of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov. Wash hands after handling

ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION

you have read and agreed to this specification sheet and upon
confirmation of your order; this
item may be non-cancelable and non-returnable.
Signature
O.g.nata.c
Company

Page 1 of 1

Date