

1. CONDUCTOR:

- 1.1 Size and Material: 12 65/30 AWG tin-plated copper wire.
- 1.2 O.D.: .0865" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Marking on the insulation: as per UL and CSA Standards.
- 2.3 O.D.: .1765" nom.
- 2.4 Color: as per order (replace X in the part number and the description by 0-9 color code).
- 2.5 Talc powder applied on the insulation.

3. PERFORMANCE:

- 3.1 Voltage rating: 15 KVDC
- 3.2 Temperature rating: 150°C
- 3.3 Flame test: VW-1 (UL)/FT1 (CSA)


4. REFERENCES:

- 4.1 UL Subject 758 (AWM), Style 3239.
- 4.2 CSA Standard C22.2 No. 127 (Equipment/Lead Wire), Type TV-15.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.							This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done: <i>Pierre Garand</i>		 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com			
1571								Date: September 8, 2008					
								Verified: <i>Carrie Lott</i>		Description: XSF45Z1265/30-X			
								Date: September 9, 2008					
UNCONTROLLED DOCUMENT									Size: A	Scale: ---	Page: 1 of 1	Code Ident. No: 57104	Specification No.: F00187-X