


3M™ ROUND CONDUCTOR FLAT CABLE, HF365 SERIES

.050" 28 AWG STRANDED, HALOGEN FREE PO



NOTE: BLUE MARKING ON ONE EDGE OF CABLE DESIGNATES WIRE #1.

2 PHYSICAL :

JACKET MATERIAL: HALOGEN FREE POLYOLEFIN (PO)
COLOR: DARK GRAY

MARKING: NONE
STANDARD: NONE
CONDUCTORS: 28 AWG 7 X 36AWG (7 X Ø .127) TINNED STRANDED COPPER

2 ELECTRICAL :

VOLTAGE RATING: USA 300V CANADIAN 150V EU: <50V
INSULATION RESISTANCE: >1 X 10¹⁰Ω/10ft. [3m]

	UNBALANCED	BALANCED
CHARACTERISTIC IMPEDANCE:	100Ω	168Ω
CAPACITANCE:	15.0 pF/ft [49.2 pF/m]	8.4 pF/ft [27.7 pF/m]
INDUCTANCE:	.15μH/ft [.49μH/m]	.24μH/ft [.79μH/m]
PROPAGATION DELAY:	1.51 ns/ft [4.95 ns/m]	1.42 ns/ft [4.66 ns/m]
VELOCITY OF PROPAGATION:	68%	72%

NOTE: UNBALANCED IS MEASURED BETWEEN GROUND-SIGNAL-GROUND CONDUCTORS.
BALANCED IS MEASURED BETWEEN CONDUCTORS WITHIN A PAIR.

2 ENVIRONMENTAL :

TEMPERATURE RATING: -40°C TO 105°C (EIA-364-32G, METHOD A, TEST CONDITION 2)
-10°C TO +105°C (UL TEMPERATURE RATING)

FLAMMABILITY RATING: UL: HORIZONTAL

HALOGEN FREE IS DEFINED AS BOTH 1) NO HALOGEN COMPOUNDS THAT ARE INTENTIONALLY ADDED TO THE PRODUCT OR USED IN THE MANUFACTURING PROCESS FOR THE PRODUCT AND 2) ANY IMPURITIES PRESENT ARE LESS THAN 900ppm BROMINE, LESS THAN 900ppm CHLORINE AND/OR LESS THAN 1500ppm TOTAL BROMINE AND CHLORINE. THE LATTER ARE THE LEVELS SET FORTH IN CERTAIN INDUSTRY STANDARDS FOR PRINTED CIRCUIT BOARDS, SUCH AS THE INTERNATIONAL ELECTROTECHNICAL COMMISSION (IEC) 61249-2-21 STANDARDS. THIS INFORMATION REPRESENTS 3M'S KNOWLEDGE AND BELIEF WHICH MAY BE BASED IN WHOLE OR IN PART ON INFORMATION PROVIDED BY 3RD PARTY SUPPLIERS TO 3M.

3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3mconnectors.com>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373

- * LOW SMOKE ZERO HALOGEN (LSZH) INSULATION. ADVANTAGES OF LSZH INSULATION ARE THE LOW SMOKE (IEC 61034-2-2005) AND LOW TOXICITY OF COMBUSTION GASES (NF X 70-100-2-2006), REDUCING THE RISK TO FIREFIGHTERS AND REDUCING THE SOOT AND CORROSION DAMAGE TO NEARBY EQUIPMENT.
- * 28 AWG WIRE ON .050 INCH CENTERS PERMITS MASS TERMINATION TO BROAD LINE OF IDC CONNECTORS.
- * ZIPPABLE FOR BRANCHING OR DISCRETE TERMINATION.

1. REGULATORY INFORMATION:
VISIT 3M.com/regs OR CONTACT YOUR 3M REPRESENTATIVE TO FIND THE RoHS COMPLIANCE STATUS OF THE 3M PART YOU ARE INTERESTED IN.
2. IN THE EVENT OF CONFLICT BETWEEN THIS DATA AND THAT CONTAINED IN THE PRODUCT SPECIFICATION, THE PRODUCT SPECIFICATION TAKES PRECEDENT.

NUMBER OF CONDUCTORS	3M PART NUMBER	DIM. "A"	DIM. "B"
04	HF365/04	.200+/- .010 [5.08]	.150+/- .007 [3.81]
06	HF365/06	.300+/- .010 [7.62]	.250+/- .007 [6.35]
08	HF365/08	.400+/- .010 [10.16]	.350+/- .007 [8.89]
09	HF365/09	.450+/- .010 [11.43]	.400+/- .007 [10.16]
10	HF365/10	.500+/- .010 [12.70]	.450+/- .007 [11.43]
11	HF365/11	.550+/- .010 [13.97]	.500+/- .007 [12.70]
12	HF365/12	.600+/- .010 [15.24]	.550+/- .007 [13.97]
14	HF365/14	.700+/- .010 [17.78]	.650+/- .007 [16.51]
15	HF365/15	.750+/- .010 [19.05]	.700+/- .007 [17.78]
16	HF365/16	.800+/- .015 [20.32]	.750+/- .011 [19.05]
18	HF365/18	.900+/- .015 [22.88]	.850+/- .011 [21.59]
20	HF365/20	1.000+/- .015 [25.40]	.950+/- .011 [24.13]
24	HF365/24	1.200+/- .015 [30.48]	1.150+/- .011 [29.21]
25	HF365/25	1.250+/- .015 [31.75]	1.200+/- .011 [30.48]
26	HF365/26	1.300+/- .015 [33.02]	1.250+/- .011 [31.75]
30	HF365/30	1.500+/- .020 [38.10]	1.450+/- .015 [36.83]
34	HF365/34	1.700+/- .020 [43.18]	1.650+/- .015 [41.91]
36	HF365/36	1.800+/- .020 [45.72]	1.750+/- .015 [44.45]
37	HF365/37	1.850+/- .020 [46.99]	1.800+/- .015 [45.72]
40	HF365/40	2.000+/- .020 [50.80]	1.950+/- .015 [49.53]
44	HF365/44	2.200+/- .020 [55.88]	2.150+/- .015 [54.61]
50	HF365/50	2.500+/- .020 [63.50]	2.450+/- .015 [62.23]
60	HF365/60	3.000+/- .020 [76.20]	2.950+/- .015 [74.93]
64	HF365/64	3.200+/- .020 [81.28]	3.150+/- .015 [80.01]

ORDERING INFORMATION

HF365/XX XX

BLANK = STANDARD
SF = SPLICE FREE

No. OF CONDUCTORS:
(SEE TABLE 1)

NOTE: AVAILABLE IN STANDARD 100FT OR 300FT ROLLS.
PLEASE SPECIFY WHEN ORDERING.
CONTACT 3M FOR AVAILABILITY OF ADDITIONAL
CONDUCTOR COUNTS AND/OR CUSTOM ROLL LENGTHS.



INCH [MM]		
TOLERANCE - UNLESS NOTED		
	.X	.XX
	±.1	±.01
	±.2	±.13
[] = DIM. FOR REFERENCE ONLY		

DESIGN REFERENCE	NEXT ASSEMBLY	REV	ECO	ISSUE DATE AND DESCRIPTION	DRFT	CHKD
				MAY 25, 2018	JNC	BM
DO NOT SCALE DRAWING	SCALE 25 1	TOLERANCES EXCEPT AS NOTED				
THIRD ANGLE PROJECTION	INTERPRET PER ASME Y14.5 - 2009	MAX SURFACE ROUGHNESS		TITLE: ROUND CONDUCTOR FLAT CABLE, .050", 28AWG STRANDED, HAL-FREE CAGE NUMBER: D78-5100-2334-0 MODEL: HF365		

78-5100-2334-0
DRAWING NUMBER
C
REV. 1
MAY 25, 2018
DATE
JNC
BM
DRFT
CHKD
MAY 25, 2018
DATE
B. MIZE
APPRV
MAY 25, 2018
DATE
© 3M COPYRIGHT 2018
This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.
Time 5/25/2018 -- UTC Drr-set
Imaged: Central Standard

