



Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372

bhanlon@huesonwire.com

C5933

Issue Date: 3/6/2019

Issue: 1

Construction

Description:	2/C 18 41/34 TC XLPE/PVC SXL Black	Diam. (In)
Component:	2 Conductors	
Conductor:	18 AWG 41/34 Tinned Copper Smoothbunch	0.045"
Insulation:	0.032" XLPE to SAE J-1128 Type SXL	0.109"
Color Code:	Dark Blue/Red (spiral stripe) + Black (No Stripe)	0.109"
Cable Assembly:	Pull in the 2 Conductors Parallel	0.190" x 0.380"
Jacket:	0.035" Flexible PVC, Oil, Moisture UV Resistant, VW-1	0.179" x 0.288"
Jacket Color:	Black	0.179" x 0.288"
Print:	No Print	

Specifications:
-40°C to +105C

Environmental Compliance
<ul style="list-style-type: none">• RoHS EU Directive 2011/65/EU (1&2) All materials used in the manufacture of this part are in compliance with EU Directive 2011/65/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.• REACH Regulation 169:• California Prop 65:
IQ190110