

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: 19-1069
Page 1 of 2 Pages

Issue: 1
Issue Date: 1/21/2019
Effective Date: 3/18/2019

A. Construction

Diameters (In)

- | | | |
|----------------|--|-------|
| 1) Component 1 | 4 X 1 PAIR | |
| a) Conductor | 18 (19/30) AWG Bare Copper | 0.050 |
| b) Insulation | 0.032" Wall, Nom. PVC/ 0.006" Wall NYLON | 0.126 |
| (1) Color Code | Alpha Wire Color Code B | |

Pair	Color	Pair	Color	Pair	Color
1	WHITE-BLACK	3	WHITE-RED		
2	WHITE-BROWN	4	WHITE-ORANGE		

- | | | |
|------------------------------|--|----------------|
| c) Pair | 2/Cond Cabled Together | |
| (1) Twists: | 3.2 Twists/foot (min) | |
| Individually Applied: | | |
| d) Shield: | Alum/Mylar Tape, 25% Overlap, Min. | |
| (1) Foil Direction | Foil Facing Out | |
| (2) Drain Wire | 18 (19/30) AWG Tinned Copper | |
| (2) Braid | Tinned Copper, 85% Coverage, Min. | |
| 2) Cable Assembly | 4 Components Cabled | |
| a) Twists: | 1.4 Twists/foot (min) | |
| b) Orientation: | Components to be arranged from INSIDE LAYER to OUTSIDE LAYER | |
| 3) Jacket | 0.065" Wall, Nom., PVC | 0.726+/- 0.037 |
| a) Color(s) | BLACK | |
| b) Print | ALPHA WIRE-* P/N 19-1069 4PR 18 AWG
(UL) WTTC 90C DRY/WET 1000V OR
(UL) TC 90C DRY/WET 600V DIR BUR SUN RES
OR MTW 18 AWG --- C(RU) AWM I/II A/B 105C
600V FT1 CE ROHS 1200VDC
* = Factory Code | |

B. Applicable Specifications

- | | | |
|----------------------|-------------------------------------|---|
| 1) UL | | |
| a) Component 1 | Unlisted Conductor | 90°C Dry / 90°C Wet / 600 V _{RMS} |
| | AWM/STYLE 1033 | 90°C / 1200 V _{DC} |
| b) Overall | UL 1277 TC | 90°C Dry / 90°C Wet / 600 V _{RMS} |
| | UL 2277 WTTC | 90°C Dry / 90°C Wet / 1000 V _{RMS} |
| | SUN RES | |
| | UL 1685 Vertical Tray Flame Test | |
| | UL 1063 MTW | 90°C Dry / 60°C Wet / 600 V _{RMS} |
| | DIRECT BURIAL | |
| | OIL RES I | |
| | EXPOSED RUN | |
| 2) CSA International | C(RU) AWM I/II A/B FT1 | 105°C / 600 V _{RMS} |
| 3) Other | | |
| a) Component 1 | ASTM-B174 Class K | |
| 4) CE: | EU Low Voltage Directive 2014/35/EU | |

C. Environmental Compliance

- | | |
|-------------------------------------|---|
| 1) CE: | EU Directive 2011/65/EU(RoHS2):
This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011 and the amending Directive 2015/863/EU of 4 June 2015. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C . |
| 2) REACH Regulation (EC 1907/2006): | This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration . |

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION

Part Number: 19-1069
Page 2 of 2 Pages

Issue: 1
Issue Date: 1/21/2019
Effective Date: 3/18/2019

D. Physical & Mechanical Properties

- 1) Temperature Range -40 to 90°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 185 Lbs, Maximum
- 4) Sunlight Resistance Yes
- 5) Direct Burial Yes

E. Electrical Properties

(For Engineering purposes only)

- 1) Voltage Rating 600/1000 V_{RMS}/1200 V_{DC}
- 2) Mutual Capacitance 36 pF/ft @ 1 kHz, Nominal
- 3) Ground Capacitance 65 pF/ft @ 1 kHz, Nominal
- 4) Characteristic Impedance 62 Ω
- 5) Inductance 0.23 μH/ft, Nominal
- 6) Conductor DCR 5.7 Ω/1000ft @20°C, Nominal
- 7) Component Shield DCR 2.24 Ω/1000ft @20°C, Nominal

F. Other

- 1) Packaging Flange x Traverse x Barrel (inches)
 - a) Bulk(Made-to-order)

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.