



IEWC.COM
 5001 South Towne Drive
 New Berlin, WI 53151
 800.344.2323

Issue Date: 4/1/2019

Issue: 1

Construction

Description:	4/C 14 41/30 BC PVC/PVC AWMN 2586	Diam. (In)
Component:	4 Conductors	
Conductor:	14 AWG 41/30 Bare Copper to ASTM B-174	0.075"
Insulation:	0.03" Premium Grade PVC Insulation	0.135"
Color Code:	Red, Blue, Black, Green/Yellow	0.135"
Cable Assembly:	Cable the 4 Conductors 3.5" LHL	0.327"
Fillers	Fibrillated polypropylene fillers for roundness (optional)	0.327"
Separator:	Tissue Paper	0.330"
Jacket:	0.03" Pressure Extruded PVC, Oil, Moisture UV Resistant, VW-1	0.390"
Jacket Color:	Black 0.390" +/- .010"	0.390"

Print: E174416 RU AWM 2586 105C 600V VW-1 --- cRU AWM I/II A/B 105C 600V FT-1

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
UL	AWM-2586	105°C	600	VW-1
Canadian cRU	AWM	105°C	600	FT-1 I/II A/B

Environmental Compliance

- RoHS EU Directive 2011/65/EU (1&2)
- REACH Regulation 169:
- California Prop 65:

IQ190145