

N21-44T-00015-R2-9UL  
4 CONDUCTOR CABLE

26 AWG TWISTED PAIR (1)  
26 AWG SINGLES (2)  
26 AWG 66/44 TINNED COPPER, 0.010" (0.009" MIN) PVC  
TO 0.039" +/- 0.002" OD-YELLOW/WHITE, YELLOW/RED  
UL AWM 1729

CABLE  
26 AWG SINGLES (2)

26 AWG SINGLES (2)  
26 AWG 66/44 TINNED COPPER, 0.010" (0.009" MIN) PVC  
TO 0.039" +/- 0.002" OD-WHITE, RED  
UL AWM 1729

CABLE  
26 AWG TWISTED PAIR (1)  
26 AWG SINGLES (2)  
FILLER: LS POLYESTER IN THE INTERSTICES

TAPE  
0.002" UNSINTERED PTFE, 50% LAP

INSULATE  
0.034" (0.031" MIN) POLYURETHANE JACKET TO 0.193"  
+/- 0.008" OD-GRAY UL AWM 20233 80C 300V

MINIMUM = 1,000 FEET

FINISHED WEIGHT = (16.91#/KFT) (0.0252KG/MTR)

\*\*\*Labeling\*\*\*

TWO OUTSIDE LABELS REQUIRED - One label on the flange, and one label  
on the side of the reel.

Spool Size: 18" PLYWOOD-B