

CERTIFIED BY:

CONDUCTOR

AWG SIZE & STRANDING: 26 AWG 19 STRANDS CLASS C
 MATERIAL: ANNEALED TINNED COPPER

INSULATION

MATERIAL: POLYPROPYLENE
 WALL THICKNESS: 0.007"
 COLOR CODE: BLACK, RED

ASSEMBLY

CABLE LAY LENGTH: 1.25" LHL
 DRAIN: 26 AWG 19 STRANDS TINNED COPPER
 BRAID: 36 AWG TINNED COPPER - 85% COVERAGE
 SEPARATOR: TISSUE WRAP - 100% COVERAGE

JACKET

MATERIAL: PRESSURE EXTRUDED POLYURETHANE
 WALL THICKNESS: 0.014"
 DIAMETER: 0.140" ± 0.005"
 COLOR: MATTE BLACK
 CONVOLUTION LEVEL: LEVEL 3 OR BETTER

MARKINGS

NONE

REGULATORY


MUST MEET RoHS REQUIREMENTS

SPOOLING

MINIMUM 1000 FT CONTINUOUS UNBROKEN LENGTH
 ON 16" UNMARKED SPOOL WITH ANYTHING OTHER THAN CTC LOGO

ALL SPOOLS MUST BE MARKED WITH CTC PART NUMBER ON
 BOTH SIDES OF SPOOL. 0.5" MIN HEIGHT.



 CONNECTION TECHNOLOGY CENTER, INC	MATERIAL	ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED TOLERANCES (UNLESS SPECIFIED) XXX ± 0.005 XX ± 0.01 X ± 0.1 ANGLE ± 2° BREAK ALL SHARP EDGES .010 MAX
	PART #: <p style="text-align: center; font-size: 1.2em;">CBP11027</p>	
DESCRIPTION: CABLE, 0.14" DIAMETER BLACK POLYURETHANE JACKET, 26 AWG TWISTED SHIELDED PAIR, BRAIDED SHIELD		NOT DRAWN TO SCALE

REV	DESCRIPTION	ECO#	DESIGNER	ENG APPROVED	DATE	MFG APPROVED	DATE
B	CHANGED SPECS TO MATCH EPN11278 BUT BLACK		LSC	AJN	6/11/2019	JDB	6/11/2019
A	FOR RELEASE		DMG	AJB	12/08/2017	JDB	12/8/2017