

**Description:** Four Conductor 18 AWG,  
Overall Plenum PVC Jacket

**Create Date:** 05/16/2019

**JM Part No:** JM58213

**Reference:** SP184C(19)X-00

<b>Components</b> Four 18 AWG, Plenum PVC Insulated Conductors	<u>Nom OD</u>
Conductor: 18 AWG, 19/30 bare copper	
Insulation: .0085" nominal wall of Plenum PVC (see color code)	.065"

**Overall Cable Construction**

Cabling: 4 conductors cabled together With 2.5" LHL  
 Jacket: .0165" nominal wall of Black Plenum PVC .190"

**Print** White Inkjet  
 E67179 4/C 18 AWG 75C (UL) CL3P OR FPLP OR C(UL)US CMP FT6 ROHS MADE IN USA  
 [Sequential Footage Marking]

**Color Code**

- |                    |                     |
|--------------------|---------------------|
| 1. Black Printed 2 | 3. Violet Printed 6 |
| 2. Red Printed 1   | 4. Orange Printed 7 |

**Requirements**

Temperature: -20°C to +75°C  
 Voltage: 300 V  
 Cable Weight: 34 lbs/Mft  
 Copper Weight: 23 lbs/Mft

Approvals:  
 UL CL3P  
 UL CMP  
 UL FPLP  
 cUL CMP FT6  
 Materials are RoHS Compliant  
 (2011/65/EU & EU 2015/863)

Written By:	ka/ba	05/16/2019	Rev. 0	Initial Issue
Revised By:				
Revised By:				