

Description: 16 AWG 4/C STR OAS CL2R, CMR, C(ETL)US FT4
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800, CSA C22.2 No. 214

Construction:

Conductor 16 26/30 Bare Copper
Insulation Polypropylene
Insulation Thickness 0.006" nom.
Insulation Colors Blk,Red,Wht,Grn
Insulation Diameter 0.070" nom.
Lay Length (Twist) 3.5" nom.
Drain Wire 24 7/32 Tinned-Copper
Shield Alum/Mylar tape

Jacket PVC
Jacket Thickness 0.015" nom.
Outside Diameter 0.204" nom.

Legend (Ink Print) **HONEYWELL P/N 2222 4C16 SHIELDED 3038058 (ETL) CL2R OR CMR C(ETL)US FT4
SUN RES (RoHS) C(ETL) FT4 W/O #XXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B
C D E F 1 2 3 4 5 6 7 8 9**

Properties

Temperature Rating -20 to 60 °C
Operating Voltage 300 Volts max.
Capacitance 40 pf/ft nom.
Impedance 40 Ohms nom.
DC Resistance 4.15 Ohms/M' at 20°C
Flame Rating UL 1666 (Riser), CSA-C22.2 No. 2556 (FT4)