

ALPHA WIRE

Part Number: 19-1476

Issue: A

Page 1 of 1 Pages

Issue Date:

4/11/2019

Cable Specification

Component 1 12 PAIR
Conductor: 20 (19/32) AWG TC
Insulation: 0.010" Wall, Nom. SR-PVC
Color Code: ALPHA WIRE COLOR CODE B
Pair: 2/Cond Cabled Together with 14 twists/foot min.

Final Assembly 12 Components with 2 twists/foot min.
Core Wrap: CM Tape, 25% Overlap, Min.
Shield: TC BRAID Shield, 85% Coverage, Min.
Drain Wire: 20 (7/28) AWG TC
Jacket: 0.032" Wall, Nom., PVC
Jacket OD: 0.490"
Jacket Color: SLATE per sample to be sent at time of order

Approvals

UL: AWM/STYLE 2464
CM
VW-1
CSA: c(UL) CMG
FT4
MIL: NONE
CE Compliant: YES
ROHS Compliant: YES
REACH Compliant: YES

Miscellaneous

Temperature: 105 C
Voltage: 300 V_{RMS}
Put Ups: 1000 FT PUTUP
Requested Quantity: 1000Ft., 3000Ft., 5000Ft.

Application Notes

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.