

## ALPHA WIRE

Part Number: 19-1783

Issue:

Page 1 of 1 Pages

Issue Date:

5/29/2019

### Cable Specification

<u>Component 1</u>	8 COND
<u>Conductor:</u>	18 (41/34) AWG TC
<u>Insulation:</u>	0.012" Wall, Nom. MPPE1
Color Code:	1 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED
<u>Component 2</u>	4 COND
<u>Conductor:</u>	12 (168/34) AWG TC
<u>Insulation:</u>	0.015" Wall, Nom. MPPE1
Color Code:	1 SOLID COLORS/ 0 STRIPED/ 0 NUMBER CODED
<u>Final Assembly</u>	2 Components
Core Wrap:	NWP Tape, 25% Overlap, Min.
<u>Jacket:</u>	0.032" Wall, Nom., PUZH
Jacket OD:	0.462" +/- 0.012"
Jacket Color:	BLACK

### Approvals

UL:	AWM/STYLE 21959 60C OIL SUNRES
CSA:	c(RU) AWM I/II A/B FT2
MIL:	NONE
CE Compliant:	YES
ROHS Compliant:	YES
REACH Compliant:	YES

### Miscellaneous

Temperature:	90 C
Voltage:	600 V <sub>RMS</sub>
Put Ups:	1000 FT PUTUP
Requested Quantity:	1000Ft.

### Application Notes

Per part number AC-HYFBATL-8C18GA4C12GA

Color Code: All black conductors

Jacket print to include customer part number and company name if needed. Please specify at time of order.

CUSTOM PRODUCTS ARE NON-CANCELLABLE & NON-RETURNABLE EXCEPT FOR MANUFACTURING DEFECTS

### PROPRIETARY NOTICE

This document and any other data disclosed herein is the sole property of Alpha Wire and may not be reproduced, used or disclosed in part or in whole without the written consent of Alpha Wire. Please note that Alpha Wire does not warrant the specifications or designs developed with regard to Form, Fit, or Functionality for any specific end use application, and that the suitability of such and any future liability associated with the manufactured items is the sole responsibility of the end user.