



IEWC.COM  
 New Berlin, WI 53151  
 800.344.2323

**Issue Date:** 6/11/2019

**Construction**

**Issue:** 1

<b>Description:</b> 2/C 20 7/28 BC XLP/PVC Round		<b>Diam. (In)</b>
<b>Component:</b>	2 Conductors	
<b>Conductor:</b>	20 AWG 7/28 Bare Copper to ASTM B-8	0.038"
<b>Insulation:</b>	0.016" XLPE to SAE J-1128 0.07" +/- .003"	0.07"
<b>Color Code:</b>	Green + White	0.07"
<b>Cable Assembly:</b>	Bunch Cable 2 Conductors with a 5" LHL	0.14"
<b>Fillers</b>	None	0.14"
<b>Drain Wire:</b>	No Drain	0.14"
<b>Binder:</b>	Non-Woven Polyester Wrapping	0.143"
<b>Jacket:</b>	0.036" PVC, Oil, Gas, Moisture and UV Resistant VW-1	0.215"
<b>Jacket Color:</b>	Black 0.215" +/- 0.010"	0.215"
<b>Print:</b>	HCD # 20/2-BLK INNER CONDUCTORS ARE 125C XLPE PER SAE J1128 AND OUTER JACKET IS 105C PVC-MEETS REQUIREMENTS OF THE UL1581 UV/SUNLIGHT RESISTANCE TEST - MADE IN USA (Month/Year) ROHS-2	
<b>Environmental Compliance</b>		
<ul style="list-style-type: none"> <li>• RoHS EU Directive 2011/65/EU (1&amp;2)</li> <li>• REACH Regulation 169:</li> <li>• California Prop 65:</li> </ul>		
		IQ190261



Issue Date: 6/11/2019  
Issue: 1

Drawing/Rotation:

