

1. CONDUCTOR (2):

- 1.1 Size and Material: 20 19/32 AWG nickel-plated copper wire.
- 1.2 O.D.: .038" nom.

2. INSULATION:

- 2.2 Extruded PTFE.
- 2.3 Surface treated with a sodium etching solution.
- 2.4 O.D.: .0695" ± .002"
- 2.5 Color code: white, white.

3. CABLING:

- 3.1 The two wires are twisted together with a 1 3/8" nominal left hand lay.
- 3.2 O.D.: .139" nom.

4. JACKET:

- 4.1 Extruded silicone rubber.
- 4.2 O.D.: .209" nom.
- 4.3 Color: black.
- 4.4 Talc powder applied on the jacket.
- 4.5 Specific gravity: 1.29 nom.
- 4.6 Hardness: 80 ± 5 Shore A.
- 4.7 Tensile strength: 1100 psi nom.
- 4.8 Elongation: 335% nom.
- 4.9 Brittleness temperature: -65°C nom.
- 4.10 Tear strength: 80 Die B nom.
- 4.11 Dielectric constant: 3.20 nom.
- 4.12 Dielectric strength: 400 V/mil nom.
- 4.13 Volume resistivity: 0.12 x 10¹⁶ ohm-cm nom.

5. PERFORMANCE:

- 5.1 Voltage rating: 600 VAC R.M.S.
- 5.2 Temperature rating: 260°C (inner wires) / -40°C to 200°C (whole cable)


6. NOTES:

- 6.1 Weight: 29.83 lbs/1000 ft nom.

CUSTOMER APPROVAL

Sign: _____

Date: _____

Engineering Change Notice No.								This specification is the property of Harbour Industries Canada Limited and may not be used or copied without the express written permission of Harbour Industries Canada Limited.	Done:	<i>Daniel Curson</i>		 Harbour INDUSTRIES 1365, boul. Industriel, Farnham, Quebec, Canada, J2N 2X3 Phone: (450) 293-5304 Fax: (450) 293-2421 Web site: www.harbourind.com							
							Date:		May 23, 2019										
							Verified:		<i>Carrie Lott</i>										
							Date:		May 23, 2019		Description:	2(EXE16N2019/32)SR 9-9/0							
UNCONTROLLED DOCUMENT A later revision of this specification may exist.									Size:	A	Scale:	---	Page:	1 of 1	Code Ident. No:	57104	Specification No.:	Q04500-S	Rev.: