



NEW ENGLAND WIRE TECHNOLOGIES

130 North Main St, Lisbon, NH 03585 USA

www.newenglandwire.com

Innovate. Create. Accelerate.

N21-44B-703-R4-2UP1
4 CONDUCTOR CABLE:

16 AWG SINGLES (4):
16 AWG 7X95/44 BARE COPPER, .010" (.009" MIN) PVC TO
.084"
+/- .002" OD TO UL AWM 1729 - WHITE, BLACK, RED, GREEN

CABLE FOUR 16 AWG SINGLES WITH 16 AWG 7X95/44 BARE
COPPER DRAIN
WIRE IN AN INTERSTICE

36 AWG TINNED COPPER SPIRAL SHIELD, 90% MIN COVERAGE

.033" (.030" MIN) MATTE BLACK PVC JACKET TO .278" +/-
.008" OD
TO UL AWM 2464 80C, 300V

TO BE PRINTED IN WHITE INK AS FOLLOWS:
"(4C/16 AWG/SHLD/HI-FLEX)
RU AWM 2464 80C 300V E42481"

MINIMUM = 1000 FEET

NOTE

OLDER PART:
LINE 1 REPLACED BY THIS PART

FINISHED WEIGHT = (72.28#/KFT) (0.1089KG/MTR)

Labeling

TWO OUTSIDE LABELS REQUIRED - One label on the flange, and one label
on the side of the reel.

Spool Size: 22" PLYWOOD