	Ĩ	PRODUCT SPECIFICATION: FW94	52			
(TEW&C)		) AWG, type K, PFA ins, unshielded, PFA jkt. ANSI color code.				
	<b>TE Wire &amp; Cable</b> The most trusted name in thermocouple wire since 1941	DRAWN: J. MAJOR	7/14/2016	REVISION	APPROVED BY	DATE
	107 North Fifth Street • Saddle Brook, NJ 07663-6167 • 888-4TE-WIRE • www.tewire.com	CHECKED:				
		CUSTOMER APP.:				
Manufacturing of	description: PFA/PFA-20-K					
<b>Construction Det</b>	ails					
Canduatar	20 AMC, collid the measurely standard and de		06.1			
Conductor	20 AWG, solid thermocouple, standard grade	, type k per ASTM E230 & ANSI MC	96.1			
Insulation	Extruded PFA.					
	Color Code: (+) Yellow, (-) Red					
Twisting of pair	The conductors lie in parallel.					
		(				
Jacket	Extruded PFA. Nominal final diameter: .068"/	2.116"				
	Color: Brown.					
Other	Temperature rating: 260 C					
	· · · · · · · · · · · · · · · · · · ·					
		The info	ormation contained in th	nis drawing is pro	oprietary property of	
		TE Wire 8	Cable. It may not be u	sed or reproduce	ed, in whole or in part	,
			without written autho	rization of TE W	ire & Cable	