



Specification Sheet

Lake Cable Part #: V182/X-09

Description: 18 AWG 2 conductor 7 strand bare copper with PVC/Nylon insulation, unshielded with an overall PVC jacket 600V control tray cable, approved for use in SUN RES DIR BUR 90°C applications.

1. Conductor

- 1.1. AWG Size & Stranding: 18 AWG 7 Strands Class B
- 1.2. Material: Annealed Bare Copper
- 1.3. Conductor Count: 2 Conductors

2. Insulation

- 2.1. Material: Polyvinylchloride & Nylon
- 2.2. Wall Thickness: 0.015" PVC & 0.005" Nylon
- 2.3. Color Code: Purple, Purple/White

3. Assembly

- 3.1. Lay Length: 2.50" LHL
- 3.2. Fillers: N/A
- 3.3. Binder: N/A
- 3.4. Shield: N/A
- 3.5. Drain Wire: N/A

4. Jacket

- 4.1. Material: Polyvinylchloride
- 4.2. Wall Thickness: 0.045"
- 4.3. Diameter: 0.260" +/- 0.020"
- 4.4. Color: White
- 4.5. Ripcord: Yes
- 4.6. Cold Bend Rating: -40°C
- 4.7. Weight: 35 lbs./Mft.

5. Markings

- 5.1. Type: Cable shall be permanently identified via surface inkjet print
- 5.2. Legend: LAKE CABLE E208309 18AWG 2C (UL) TC PVC/NYLON 600V 90C DRY/WET PVC JACKET SUN RES DIR BUR FT4 "ROHS COMPLIANT" MADE IN USA
- 5.3. Footage Markers: Yes

6. Standards

- 6.1. Refer to NEC (NFPA 70) article 336 for installation guidelines
- 6.2. Cable is suitable for use in Class I Division 2 hazardous locations
- 6.3. UL listed as Type TC per UL Standard 1277 for tray cables
- 6.4. UL approved for Direct Burial and Sunlight Resistant applications
- 6.5. Cable meets UL 1581 & 1202 (FT-4) 70,000 BTU/HR & ICEA T-29-520 210,000 BTU/HR requirements
- 6.6. Meets ICEA S-73-532, where applicable
- 6.7. Cable meets RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive & RoHS 3 2015/863/EU Directive
- 6.8. Cable is REACH compliant per Regulation (EC) No 1907/2006 Updated June, 27 2018
- 6.9. Made in the USA
- 6.10. **⚠ WARNING:** This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov. *Wash hands after handling*

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

Date

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION