


SUPER-PAAR-TRONIC 340-C-PUR

cable for drag chains, halogen-free, EMC-preferred type, meter marking



HELUKABEL SUPER-PAAR-TRONIC 340-C-PUR 8x2x0,5 QMM E 170315 AWM STYLE
20233 20 AWG 16C VW-1 AWM I/II A/B 80°C 300V FT1/49854 001070044 CE

Technical data

- Special drag chain cable, stranded in pairs
- **Temperature range**
flexing -30°C to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage**
300 V
- **Test voltage**
core/core 1500 V
core/screen 1000 V
- **Insulation resistance**
min. 100 MΩm x km
- **Mutual capacitance**
core/core approx. 60 nF/km
- **Minimum bending radius**
for permanent bending
flexing
at 0,25 mm²: 7,5x cable Ø
at 0,5 - 1 mm²: 10x cable Ø
fixed installation
at 0,25 mm²: 4x cable Ø
at 0,5 - 1 mm²: 5x cable Ø
- **Coupling resistance**
max. 250 Ωm/km
- **Radiation resistance**
up to 100x10⁶ cJ/kg (up to 100 Mrad)

Cable structure

- Bare copper conductor, extra fine wire, acc. to DIN VDE 0295 cl.6, col. 4, BS 6360 cl.6 and IEC 60228 cl.6
- Core insulation of PP
- Core identification to DIN 47100
- Cores stranded in pairs, pairs stranded torsion-free in layers with optimal lay length
- Wrapping over the outer layer
- Braided screen of tinned Cu wires, coverage approx. 85%
- Core wrapping with fleece
- Outer sheath of **full polyurethane** compound type TMPU to DIN VDE 0207-363-10-2 / DIN EN 50363-10-2 and acc. to UL Std.1581 tab.50.227
- Sheath colour: grey (RAL 7001)
- With meter marking

Properties

- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- Halogen-free
- Weather, ozone and UV resistant
- Chemical resistance to solvents, acids, alkalis and hydraulic fluids

Tests

- PUR outer sheath, flame retardant acc. to DIN VDE 0482-332-1-2, DIN EN 60332-1-2, IEC 60332-1-2 (equivalent DIN VDE 0472 part 804 test method B)
- Oil resistance acc. to DIN VDE 0473-811-404/ DIN EN 60811-404

Note

- AWG sizes are approximate equivalent values. The actual cross section is in mm².

Advantages

- Very high resistance to mechanical stresses
- Very good alternating bending strength
- High tear, abrasion and impact resistance, even at low temperatures

Application

Stranded in pairs, these fully-screened special drag chain cables can also be used where external, high-frequency interference influences pulse transfer. They are used for permanently flexible stresses in machine and tool building, in robot technology, on constantly moving machine components and for extended use in multi-shift operations. Developed to state-of-the-art technology, these highly flexible data cable, with a cut resistant and low-adhesion PUR outer sheath guaranteeing optimal service life and extremely good cost efficiency. This two-approvals single-core cable is preferred for use in export-oriented mechanical engineering, in machine tools, production lines and systems engineering. Guaranteed extended use in multi-shift operations with extremely high bending stresses. For applications which go beyond standard solutions we recommend for our especially developed enquiry sheet for energy guiding systems. Before installation in cable trays please read the instructions. Further technical details see selection table for drag chain cables, see chapter "Technical Informations".

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Part no.	No.pairs x no.cores x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
49830	1 x 2 x 0,25	24	4,8	14,0	26,0
49831	2 x 2 x 0,25	24	6,7	32,0	61,0
49832	3 x 2 x 0,25	24	7,1	38,4	70,0
49833	4 x 2 x 0,25	24	7,6	43,2	82,0
49834	5 x 2 x 0,25	24	8,3	51,5	99,0
49835	6 x 2 x 0,25	24	9,0	71,8	126,0
49836	8 x 2 x 0,25	24	10,5	74,4	147,0
49837	10 x 2 x 0,25	24	11,9	90,0	179,0
49838	14 x 2 x 0,25	24	12,7	111,2	210,0
49839	1 x 2 x 0,34	22	5,1	20,0	35,0
49840	2 x 2 x 0,34	22	7,2	41,0	80,0
49841	3 x 2 x 0,34	22	7,6	52,2	100,0
49842	4 x 2 x 0,34	22	8,3	59,1	118,0
49843	5 x 2 x 0,34	22	9,0	67,0	134,0
49844	6 x 2 x 0,34	22	9,9	86,4	162,0
49845	8 x 2 x 0,34	22	11,9	107,5	214,0
49846	10 x 2 x 0,34	22	13,9	131,0	270,0
49847	14 x 2 x 0,34	22	14,1	150,0	304,0
49848	1 x 2 x 0,5	20	5,8	22,5	47,0
49849	2 x 2 x 0,5	20	8,4	53,0	100,0
49850	3 x 2 x 0,5	20	9,0	72,8	131,0

Part no.	No.pairs x no.cores x cross-sec. mm ²	AWG-No.	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
49851	4 x 2 x 0,5	20	10,0	75,6	149,0
49852	5 x 2 x 0,5	20	11,0	85,7	169,0
49853	6 x 2 x 0,5	20	11,8	103,0	181,0
49854	8 x 2 x 0,5	20	14,2	148,4	274,0
49855	10 x 2 x 0,5	20	16,5	180,0	332,0
49856	14 x 2 x 0,5	20	16,9	218,3	390,0
49857	1 x 2 x 0,75	19	6,2	35,2	56,0
49858	2 x 2 x 0,75	19	9,2	61,4	102,0
49859	3 x 2 x 0,75	19	9,8	87,1	144,0
49860	4 x 2 x 0,75	19	11,2	95,2	160,0
49861	5 x 2 x 0,75	19	12,2	115,0	193,0
49862	6 x 2 x 0,75	19	13,2	137,1	216,0
49863	8 x 2 x 0,75	19	15,6	184,4	327,0
49864	10 x 2 x 0,75	19	18,4	259,8	451,0
49865	14 x 2 x 0,75	19	18,9	318,4	521,0
49866	1 x 2 x 1	18	6,7	42,0	64,0
49867	2 x 2 x 1	18	10,0	73,0	120,0
49868	3 x 2 x 1	18	10,8	93,6	160,0
49869	4 x 2 x 1	18	11,7	117,8	184,0
49870	5 x 2 x 1	18	13,2	139,0	217,0

Dimensions and specifications may be changed without prior notice. (RN05)