

UNITRONIC® FD CP (TP) plus

Continuous flex 250V multi-pair PUR industrial communication cable; shielded

LAPP KABEL STUTTGART UNITRONIC® FD CP (TP) plus



UNITRONIC® FD CP (TP) plus is a Type CMX approved multi-pair communication cable designed for continuous flexing industrial signal and data applications. The tear-resistant polyurethane jacket provides excellent service life in harsh environments against most oils, solvents, and coolants. It has a tinned copper braid shield for EMI resistance.

Recommended applications

High-speed automated equipment; robotics; CNC and multi-axis cutting equipment; other cable track applications

Approvals



Construction

Conductors: finely stranded bare copper

Insulation: polyolefin

Pairs: conductors are paired and twisted together; non-woven wrapping

Shielding: tinned copper braid

Jacket: specially formulated polyurethane; gray

Application advantage

- UL/c(UL) CMX approved
- Flexible at -40°C
- Resistant to oils, solvents, and coolants
- Abrasion-resistant & halogen-free jacket
- Resistant to microbes and hydrolysis

Cable attributes		page 648	
OIL	OR-05	FLAME	FR-02
MOTION	CF-02	MECH.	MP-05

Complete the installation	
SKINTOP® MS-SC page 522	EPIC® connectors page 284

ÖLFLEX® CONNECT solution	
	ÖLFLEX® CONNECT CABLES page 605

Technical data

Minimum bend radius: - for continuous flexing:	7.5 x cable diameter	Mutual capacitance: - up to 0.5 mm ² : - up to 1.0 mm ² :	18 pF/ft 21 pF/ft
Temperature range: - for continuous flexing: - AWM: - CMX:	-40°C to +80°C up to +80°C up to +75°C	Inductance:	approx. 0.65 mH/km
Nominal voltage:	250V (not for power)	Conductor stranding:	extra fine wire per VDE 0295
Test voltage: - conductor/conductor: - conductor/shield:	1500V 500V	Color code:	DIN 47100: chart 7, page 682
		Approvals:	UL: AWM 21576 CMX Canada: c(UL) CMX cRU AWM I/II A/B FT2 Additional: CE & RoHS

UNITRONIC® FD CP (TP) plus

Part number	Number of pairs	Nominal outer diameter in mm		Copper weight lbs/mft	Approx. weight lbs/mft	SKINTOP® MS-SC PG thread
26 AWG (0.14 mm²)						
0030910	2	0.232	5.9	13	28	53112210
0030911	3	0.244	6.2	16	36	53112210
0030912	4	0.264	6.7	18	40	53112210
0030913	5	0.287	7.3	25	50	53112220
0030914	6	0.295	7.5	33	61	53112220
0030915	8	0.346	8.8	37	73	53112220
0030916	10	0.398	10.1	40	81	53112230
24 AWG (0.25 mm²)						
0030962	1	0.185	4.7	9	18	53112210
0030919	2	0.260	6.6	22	40	53112220
0030920	3	0.276	7.0	26	48	53112220
0030921	4	0.299	7.6	29	57	53112220
0030922	5	0.335	8.5	35	69	53112230
0030923	6	0.346	8.8	48	88	53112230
0030924	8	0.406	10.3	50	104	53112240
0030925	10	0.465	11.8	60	125	53112240
0030926	14	0.472	12.0	75	147	53112240
22 AWG (0.34 mm²)						
0030963	1	0.201	5.1	13	24	53112210
0030928	2	0.287	7.3	28	54	53112220

Part number	Number of pairs	Nominal outer diameter in mm		Copper weight lbs/mft	Approx. weight lbs/mft	SKINTOP® MS-SC PG thread
0030929	3	0.315	8.0	35	68	53112220
0030930	4	0.343	8.7	40	80	53112230
0030932	6	0.394	10.0	58	111	53112230
0030934	10	0.539	13.7	88	184	53112250
20 AWG (0.5 mm²)						
0030964	1	0.232	5.9	15	32	53112210
0030937	2	0.327	8.3	34	67	53112230
0030938	3	0.346	8.8	48	87	53112230
0030939	4	0.386	9.8	50	99	53112230
0030940	5	0.421	10.7	57	113	53112240
0030941	6	0.445	11.3	67	130	53112240
0030942	8	0.520	13.2	97	191	53112250
0030943	10	0.598	15.2	118	230	53112260
0030944	14	0.610	15.5	145	269	53112260
18 AWG (1 mm²)						
0030955	1	0.248	6.3	28	48	53112210
0030956	2	0.390	9.9	49	87	53112230
0030957	3	0.413	10.5	63	114	53112240
0030958	4	0.465	11.8	79	137	53112240
0030959	5	0.516	13.1	93	159	53112250

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values.